




Isotto 21kw Pellet Boiler Cooker



- A = Ø 80 mm Scarico fumi / Flue / Cheminée / Rauchabzug / Evacuación de humos / Descarga de fumos
- B = Ø 48 mm Ingresso aria primaria / Primary air inlet / Entrée d'air primaire / Primärlufteinlass / Entrada aire primario / Admissão de ar primário
- C = Ø 80 mm Scarico fumi superiore / Flue top / Haut de fumée / Top Abgasstutzen / Salida humos superior / Descarga de fumos superior
- D = 3/4 Ritorno riscaldamento / Heating return / Retour chauffage / Heizungsrücklauf / Retorno calentamiento / Retorno aquecimento
- E = 3/4 Andata riscaldamento / Heating flow / Départ chauffage / Heizungs-vorlauf / Ida calentamiento / Partida do aquecimento
- F = 1/2 Carico/scarico impianto / System load/discharge / Remplissage/vidage installation / Be-/Entladen der Anlage / Carga/Descarga instalación / Carga/descarga sistema

Technical Data

Total heat output: max 21,0 kW – min 7,3 kW
 Nominal heat output: max 18,5 kW – min 7,0 kW
 Water heat output: max 15,5 kW – min 5,5 kW
 Energy Efficiency Class: A++
 Efficiency: Pmax 93,5% – Pmin 95,5%
 CO emission at 13% O2: Pmax 0,011% – Pmin 0,015%
 Pellet consumption: max 4,3 kg/h – min 1,5 kg/h
 Reservoir capacity: 20 kg
 Heatable room volume: 290 – 390 mc
 Boiler water content: 23 l
 Minimum distances from walls: side & rear 5mm, front 1000 cm
 Dimension: L980 x W615 x H920mm
 Weight: 250 kg
 Steel combustion chamber
 Stainless steel brazier
 Oven dimensions: L 300 x W385 x H280mm
 Complies with: EN14785 - BImSchV II - LRV/VKF - BAFA
 WIFI module for remote control: Optional
 Sliding drawer for ash removal
 Fume outlet: Top - Rear

Features

Front glass door with black etching
 Stainless steel oven
 Removable tray holder guides
 Aluminium tray supplied
 Tray holder grille supplied
 Oven temperature controlled via display (120°-240°C)
 5 operating power levels
 Menu display in 6 languages
 Can be built in or free standing
 Removable ash tray for ash removal
 Upper - rear smoke extraction
 Remote control supplied
 Safety thermostat
 Suitable for external thermostat
 Safety Manostat
 Timer Thermostat
 Expansion tank, Pump & Safety valve

Hamco

STOVES

Hamco Heating Ltd
 Cloncollig
 Church Road
 Tullamore
 Co. Offaly
 05793 21302
info@hamco.ie
www.hamco.ie